



HMG⁺

General purpose steel doors, available as single, leaf and a half, and double doorsets. An extensive selection of optional extras, vision panels and louvres, means every door can be tailored to suit individual specifications. HMG⁺ doors are also available with acoustic and FD240 fire rating, either combined or independently.



HMG¹

An outward opening single door design, certified to Level 1. Featuring many of the benefits of HMG⁺, the HMG¹ has the added advantage of independent third party testing. These doors are durable, and designed for internal and external use, to cope with high traffic levels. These doors are available with FD240 fire rating.



HMG²

Independently tested and certified to Level 2, HMG² is ideal for locations which require a high level of security against opportunistic attack, and has proven popular with utilities clients for remote access and substation sites. HMG² doors provide an economical choice, without compromising on security, and are also available with an acoustic or FD240 fire rating.



HMG³

HMG³ is an outward and inward opening door design, independently tested and certified to Level 3. Available with the UK's largest range of Level 3 options, including certified locking options, louvres, and vision panels. Suitable for all personnel, fire exit, access control and utility applications. These doors are also available with FD240 fire rating.



HMG⁴

Offering our highest level of attack resistance, HMG⁴ inward and outward opening doorsets are independently certified to Level 4. Suitable for locations requiring the highest level of security, such as banks, high value retail establishments, and government buildings. These doors are available with FD240 fire rating.



HMG^{FD}

Our range of fire rated doors are CERTIFIRE accredited to FD240, with optional certification from Level 2 to Level 4. To achieve certification, our doors were subjected to a furnace test, withstanding temperatures of up to 1100°C for a period in excess of four hours. A range of HMG^{FD} doorsets are also available with an acoustic rating.



HMG^{SB}

HMG^{SB} doors are available with optional certification from Level 1 to Level 4, with the added benefit of an FD240 fire rating, where required. Designed to be installed at remote sites where vandalism is expected, HMG^{SB} is available with a range of options specifically developed to suit substations, including ventilation options, lift-off hinges, earthing points, and padlockable shrouds.



HMG^{FL}

Our HMG^{FL} range provides flood defence doors, successfully tested to PAS 1188-1:2014. Combining both flood resistance and security, HMG^{FL} doors are available with optional Level 2 to Level 4. Particularly suitable for the utilities sector, and other unmanned locations where security and flood measures are required. Access hatches can be integrated into certain HMG^{FL} doorsets.